

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
5 August 2004 (05.08.2004)

PCT

(10) International Publication Number
WO 2004/065873 A1

(51) International Patent Classification⁷:
F28F 9/013, F22B 37/20

F28D 7/06,

(74) Agents: SINISCALCO, Fabio et al.; Jacobacci & Partners S.p.a., Via Senato, 8, I-20121 Milano (IT).

(21) International Application Number:

PCT/IT2003/000358

(22) International Filing Date: 10 June 2003 (10.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

MI2003A000070 17 January 2003 (17.01.2003) IT

(71) Applicant (for all designated States except US): RUTHS S.p.A. [IT/IT]; Via Rivarolo 183-R, I-16161 Genova (IT).

(72) Inventor; and


(75) Inventor/Applicant (for US only): CASTELLO, Marco
[IT/IT]; C/O Ruths S.p.A., Via Rivarolo 183-R, I-16161
Genova (IT).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: HEAT EXCHANGE UNITS



(57) Abstract: A heat exchange unit (4', 4", 4'''), adapted to performing heat exchange between first and second fluids at different temperatures, comprises a heat exchange apparatus (6) provided with a tube bundle (8), crossed internally by said first fluid, and containing means (10) of the second fluid, adapted to receiving the exchange apparatus (6) so that at least one portion of the tube bundle (8) is externally surrounded by the second fluid. The exchange apparatus (6) further comprises connection means (9) which are structurally separate from said retainer means (10) and to which one end of the tube bundle (8) is operatively connected.

WO 2004/065873 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

Heat exchange units

The present invention relates to a heat exchange
5 unit suitable for performing heat exchange between at
least two fluids at different temperatures.

Said exchange units are typically used to exchange
the energy possessed by a flow of warm gases, i.e. at a
higher temperature, originating from an industrial
10 process, to a cold fluid, i.e. at a lower temperature,
circulating inside heat exchange elements that comprise
the units.

In particular, gases originating from industrial
combustion plants are frequently used as the flow of warm
15 gases.

The coolant contained inside the elements of such
systems is usually water or saturated or superheated
water vapour, in a pressure range typically between 10
and 80 bar and a temperature range typically between
20 150°C and 500°C.

The warm gases, on the other hand, have a
temperature that usually varies between 100°C and 1200°C
approximately and, given that they originate from
industrial processes of combustion of urban/industrial
25 waste, they contain ashes diffused within their mass,

typically in a percentage that can vary between 0.5 gr/Nm³ and 20 gr/Nm³.

In heat exchange units it is known to provide a tube bundle, which is simultaneously crossed on the inside by
5 a first liquid at a lower temperature, known as the coolant, and surrounded externally by a second fluid, at a higher temperature, typically a gas.

However, the ashes contained in the warm gases tend to soil the heat exchange surfaces of the heat exchange
10 elements, i.e. the outer surfaces of the tubes of the tube bundle, thus hindering the heat exchange between the two fluids and irremediably compromising the performance of the units.

For this reason it is periodically necessary to shut
15 down and clean the units, in order to recover optimal working conditions of the same.

Cleaning operations include cooling the unit, the replacement of the parts to be replaced by destructive cuts and the elimination of dust from the surface by
20 means of mechanical abrasion or shaking.

The maintenance operations in any case require technical shutdown times in the order of several weeks, and considerably affect the plants' overhead costs, considering that such maintenance operations are
25 performed with a frequency equal to approximately three

times per year.

The need is felt for a heat exchange unit that permits efficient cleaning operations and that is then able to operate continuously for the longest possible
5 period of time, thus reducing the times and frequency of maintenance operations.

The object of the present invention is to provide a heat exchange unit capable of solving the abovementioned state of the art drawbacks.

10 This object is achieved by a heat exchange unit according to claim 1.

Further characteristics and the advantages of the heat exchange unit according to the present invention will result from the following description of a non
15 limiting exemplary embodiment of this heat exchange unit, wherein:

Figure 1 illustrates a front view of a heat exchange unit according to one embodiment of the present invention;

20 Figure 2 illustrates a side view of the unit from Figure 1 from the side of arrow II in figure 1;

Figure 3 illustrates a side view of the heat exchange unit from figure 1, from the side of arrow III in figure 1;

25 Figure 4 illustrates a plan view of the heat

exchange unit from figure 1;

Figure 5 illustrates a detail in partial section of figure 1;

Figure 6 illustrates a section of the unit from figure 5 taken along the line VI-VI of figure 5;

Figure 7 illustrates a section of the unit from figure 5 taken along the line VII-VII of figure 5;

Figure 8 illustrates a section of the unit from figure 2 along taken the line VIII-VIII of figure 2;

Figure 9 illustrates a section of the unit from figure 8 taken along the line IX-IX of figure 8;

Figure 10 illustrates an enlarged detail of the unit from figure 9;

Figure 11 illustrates a section of the unit from figure 8 taken along the line XI-XI of figure 8;

Figure 12 illustrates a front view of a heat exchange unit according to a further embodiment of the present invention;

Figure 13 illustrates a side view of the unit from figure 12 from the side of arrow XIII in figure 12;

Figure 14 illustrates a side view of the heat exchange unit from figure 12 from the side of arrow XIV in figure 12;

Figure 15 illustrates a section of the unit from Figure 14 taken along line XV-XV of figure 14;

Figure 16 illustrates a section of the unit from Figure 14 taken along line XVI-XVI of figure 14;

Figure 17 illustrates a plan view of the heat exchange unit from figure 12;

5 Figure 18 illustrates a further plan view of the heat exchange unit from figure 12;

Figure 19 illustrates a side view of the unit from Figure 12;

10 Figure 20 illustrates an enlarged detail of the unit from figure 12;

Figure 21 illustrates a further side view of the unit from figure 12;

15 Figure 22 illustrates a front view of a heat exchange unit according to a further embodiment of the invention;

Figure 23 illustrates a side view of the heat exchange unit from figure 22;

Figure 24 illustrates a section of the unit from figure 23 taken along the line XXIV-XXIV of figure 23;

20 Figure 25 illustrates a further side view of the heat exchange unit in figure 22;

Figure 26 illustrates a section of the unit from figure 25 taken along the line XXVI-XXVI in figure 25;

25 Figure 27 illustrates a section of the unit from figure 25 taken along line XXVII-XXVII in figure 25;

Figure 28 illustrates a plan view of the unit from figure 22;

Figure 29 illustrates a further front view of the unit from Figure 22;

5 Figure 30 illustrates a plan view of a steam production plant comprising heat exchange units according to the invention;

Figure 31 illustrates a side view of the plant from Figure 30 from the side of arrow XXXI in figure 30.

10 With reference to the annexed figures, 4', 4'', 4''' globally refer to a heat exchange unit, which is suitable for performing heat exchange between first and second fluids at different temperatures.

In particular, 4' refers to a vaporiser heat
15 exchange unit, as illustrated in figures 1-11; 4'' to a superheater heat exchange unit, as illustrated in figures 12-21; 4''' to a economiser heat exchange unit, as illustrated in figures 22-29.

The definitions of vaporiser, superheater and
20 economiser heat exchange unit apply depending on whether the fluid that runs through the bundle of tubes is saturated steam, superheated steam or water, respectively.

The elements or parts of elements common to the
25 various embodiments described below will be indicated

using the same numerical references.

With reference to figures 1-11 of the vaporiser heat exchange unit 4', the heat exchange unit comprises a heat exchange apparatus 6 provided with a tube bundle 8, 5 suitable for being crossed internally by said first fluid, connecting means 9 for connecting the tube bundle 8 to the exchange apparatus 6, and containing means 10 for said second fluid which are suitable for receiving said exchange apparatus 6 in such a way that at least a 10 portion of said tube bundle 8 is externally surrounded by said second fluid.

According to a possible embodiment, said tube bundle 8 preferably extends along a prevalent direction Z.

Preferably, said prevalent direction Z is 15 substantially perpendicular to a base plane A on which the unit rests.

In the examples illustrated in the figures, the base plane A is horizontal and the prevalent direction Z is vertical.

20 In relation to a plane substantially perpendicular to the prevalent direction Z and therefore parallel to the base plane A, a direction X and a direction Y are observed, which are perpendicular to one another.

The tube bundle 8 comprises a plurality of tubes 25 parallel to one another, which, according to a possible

embodiment substantially extend in a vertical direction, i.e., perpendicular to said base plane A of the unit and parallel to said prevalent direction Z.

The tubes of the tube bundle 8 are suitable for being crossed internally by a first fluid such as water (economiser unit, fig. 22-29) or a saturated steam (vaporiser unit, fig. 1-11) or superheated steam (superheater unit, fig.12-21), having an approximate temperature of, within normal ranges of use of heat exchange units, between 150°C and 500°C and a pressure of between 10 bar and 80 bar.

Said tubes are preferably made of metal materials, which are able to guarantee the mechanical and thermal resistance of the tubes to normal operating conditions, as well as an adequate heat exchange coefficient, without in any case requiring excessive thicknesses of the tube walls, in order to avoid unnecessarily weighing down the structure of the bundle.

Advantageously, at an upper end 12 of the tube bundle 8, i.e. an end of the bundle facing away from the base plane A of the exchange unit 4 along said prevalent direction Z, said exchange apparatus 6 comprises at least one distribution manifold 14, fluidically connected to said tube bundle 8. In a preferred embodiment, such as that shown in figure 6, said exchange apparatus 6 is

provided with two distribution manifolds 14 which are structurally separate from one another, which extend in a linear way along said direction Y, at the ends of the tube bundle 8 which are opposite to said direction X.

5 Each of the distribution manifolds 14 comprises an inlet 16 designed to receive and direct the first fluid inside the manifold. In one embodiment each of said inlet 16 is connected by an angular joint to the corresponding distribution manifold 14, in such a way as
10 to extend along said direction X, perpendicular to direction Y.

 In other words the distribution manifolds 14 are located at opposite ends of the tube bundle along direction X, with the respective inlets 16 on the same
15 side of the bundle relative to direction Y.

 Each distribution manifold 14 is fluidically connected by a plurality of tubes of the tube bundle in such a way as to distribute a fluid in the same tubes through said inlets 16.

20 Advantageously, as shown in figure 6, in at the upper end 12, the heat exchange apparatus 6 comprises a collection manifold 18, suitable for directing a fluid flowing out of the tube bundle, through an outlet 20.

 According to one possible embodiment, illustrated in
25 figures 1 and 2, said exchange apparatus 6, in at a lower

end 22, facing the base plane A of the exchange unit 4 relative to prevalent direction Z, comprises at least one lower manifold 24, fluidically connected with the tubes of the tube bundle.

5 Preferably a plurality of lower manifolds 24 is provided. The lower manifolds 24, distribution manifolds 14 and collection manifolds 18 are connected to the tubes of the tube bundle, preferably by welding, thus guaranteeing fluidic connection.

10 Said manifolds 14,18,24 constitute a hydraulic circuit, in other words they are fluidically connected to one another and permit the circulation of the first heat exchange fluid therein, so that this fluid can enter the bundle through said inlets 16, circulate in the tube
15 bundle following a predetermined path of the tubes, illustrated with arrows F in figure 1, and flow out of the bundle by at least outlet 20.

Advantageously, said at least one inlet 16 and said at least one outlet 20 are positioned on the same side of
20 the tube bundle 8, i.e. at said upper end 12.

In other words, the inlets and outlets of the tube bundle are located at the upper end 12 of the bundle.

According to a further embodiment, illustrated for example in figures 12-29, for both the superheater unit
25 and the economiser unit, the tubes of the tube bundle

extend as a coil along said prevalent direction Z.

In particular, the tubes extend prevalently in a direction parallel to prevalent direction Z and perpendicular to the base plane A of the unit, for example according to a vertical direction, from the upper end 12 to the lower end 22 of the tube bundle and vice versa.

The tubes include straight lengths, according to one embodiment, directed along the prevalent direction Z, connected to one another by curves or sines or circumference arches extending in a substantially perpendicular direction to said prevalent direction Z. In other words, the first fluid inside said coil, having travelled a straight length of tube in one direction, having reached one end of the bundle, then travels a curved stretch of tube and changes direction, i.e. it travels, in the opposite direction, a subsequent straight length of an adjacent tube, and so on.

According to one advantageous embodiment, each coil of said tube bundle, relative to a plane perpendicular to said prevalent direction Z and therefore substantially parallel to said base plane A, in turn extends along a curve that forms a series of alternatively protruding and re-entrant angles, or following a curve which forms a series of alternating concave and convex arches.

In other words, in relation to a direction parallel to said direction X or Y, each tube of the coil of the tube bundle is staggered in relation to the consecutive adjacent tube, so that each tube only partially overlaps
5 the consecutive adjacent tube.

Advantageously by staggering consecutive adjacent tubes by a quantity not less than the diameter of the tubes themselves, it follows that in relation to a direction X or Y, two consecutive adjacent tubes do not
10 overlap.

In reference to figures 1-29 and therefore to the three possible embodiments explicitly illustrated, said tube bundle 8 is advantageously structurally connected to a collection tank 26 of the heat exchange apparatus 6.

15 Said collection tank 26 is located at the upper end 12 of the tube bundle 8 and, according to one possible embodiment, is made according to a substantially hollow, box-shaped structure, in such a way as to enclose and surround said upper end 12 of the heat exchange apparatus
20 6.

The collection tank 26 comprises a shell 28 which constitutes a lateral surface of the tank, a lid 30 and a base 32, which close the opposite ends of the shell.

Said lid 30 and said base 32 are fixed to the shell
25 28, in order to constitute a closed box-shaped structure

and they extend substantially along planes parallel to the base plane A and perpendicular to the prevalent direction Z of the tube bundle.

According to one embodiment, the collection tank 26,
5 at the inner surfaces of the shell 28, of the lid 30 and the base 32, i.e. the surfaces facing the inner enclosed volume of the tank, comprises insulation means and preferably insulating material panels 33, for example in ceramic material.

10 According to one possible embodiment, the lid 30 comprises at least one crosspiece 34 and an inspection hatch 36 for inspecting the exchange apparatus 6.

Said base 32 of the collection tank 26 is crossed by the tube bundle and therefore has the configuration of a
15 drilled plate, i.e. it has holes with a diameter no smaller than the external diameter of the tubes of the tube bundle and such as to not allow the leakage of gas inside the tank.

Said crosspiece 34 is advantageously adapted to
20 support the tube bundle 8.

According to one embodiment, the connection means 9 connect the upper end 12 of the tube bundle 8 to said crosspiece 34.

According to a preferred embodiment, said connection
25 means 9 advantageously comprise hooks 44 adapted to

provide a link at least in a vertical direction, i.e. parallel to said prevalent direction Z, for said tube bundle 8.

Advantageously said hooks 44 create a connection
5 between said crosspiece 34 and the distribution manifolds 14 of the exchange apparatus.

Preferably said hooks 44 comprise a ring closed around said crosspiece 34.

According to a preferred embodiment said hooks 44
10 perform a connection between the crosspiece 34 and the distribution manifolds 14 of the tube bundle 8.

Therefore the tube bundle 8 is fixed to the heat exchange apparatus 6 exclusively at one extremity, i.e. with the exception of said end, the bundle is not fixed
15 to any other structural element, i.e. the weight of the bundle itself rests entirely on the suspension systems which are present at an upper end 12 of the tube bundle 8.

In other words the tube bundle is bound at one end
20 in such a way as to remain suspended, i.e. maintaining a substantially parallel direction to the prevalent direction Z.

According to further embodiments, it is possible to provide hooks in a number of parts welded together or
25 connected by threaded connection means, it is possible to

provide protruding elements in relation to said crosspiece and on which the tube bundles are hung.

Moreover it is possible to provide connection means that extend along a perpendicular direction to said prevalent direction Z, such as for example shelves protruding from the interior of said tank and to which said tube bundle is hung.

Advantageously inside said collection tank 26, the heat exchange unit 26 also comprises shaking means 51, better described below, adapted to shake the tube bundle 8 in order to perform cleaning operations on the same.

Advantageously the exchange apparatus 6 comprises hooking means 46, located at the end of the tube bundle 8 operatively connected to the connection means 9.

According to a preferred embodiment said hooks 46 comprise at least one eyebolt 47, adapted to perform a hooking with suitable hoisting instruments, in order to consent the handling of the tube bundle 8.

The heat exchange unit 4 comprises the containing means 10 suitable for receiving the exchange means 6 therein so that at least one portion of the tube bundle 8 is externally surrounded by the second fluid.

Said containing means 10 preferably extend along the prevalent direction Z of the tube bundle 8 so as to surround and enclose the bundle itself.

Said heat exchange apparatus 6 is advantageously rested on said containing means 10. By the term rested it is intended that the exchange means 6 rests on a portion of the containing means weighing it down with its weight, and is therefore supported by the same, without further links.

According to one possible embodiment, in order to guarantee a fluid seal between exchange means 6 and the containing means 10 so that the gases do not leak into the environment outside the exchange unit 4, advantageously, at an interface between the exchange apparatus 6 and the containing means 10, a frame 52, which is preferably part of the tank 26, is interposed.

According to a preferred embodiment, said frame 52 perimetally surrounds the base 32 of the collection tank 26.

Preferably, the frame 52 has a 'C'-shaped section, so that the distance between the two ends of the 'C' is not less than a height of an outer edge 54 of the base 32 taken along a direction parallel to the prevalent direction Z.

Advantageously said frame is suitable to being fitted around the outer edge 54 of the base 32, in other words, a shape coupling is provided between the C-shaped section and the outer edge of the base 32.

According to one possible embodiment, an insulating plate 56, preferably in ceramic material, is placed over said base 32 in order to rest on said base 32 inside the collection tank 26.

5 Said exchange apparatus 6 is at least partly received in the containing means 10.

Advantageously, the containing means 10 comprise a casing 48 that surrounds the tube bundle and that performs conveyance of the fumes towards the tube bundle
10 8, according to a direction substantially perpendicular to the prevalent direction Z of the tube bundle 8, for example indicated by the arrow F' in figure 2.

Advantageously said casing 48 terminates at one end with a collar 50 extending along the perimeter of the end
15 of the casing.

Preferably said collar 50 extends along a perimeter that follows and partially contains the outer edge 54 of the base of the collection tank.

Due to the fact that the outer edge 54 of the base
20 32 is at least partially comprised inside the area delimited by the collar 50, a link is made in the prevalent direction Z between the exchange apparatus and the containing means.

In other words, the exchange apparatus 6 is rested
25 on the collar 50 of the containing means 10.

According to one embodiment, advantageously, seals (not illustrated), preferably in ceramic fibre, are interposed between the collar 50 and the base 32 in order to guarantee a fluid seal.

5 According to a further embodiment the collar 50 receives the frame 52 of the base 32 in tight stroke.

According to one embodiment, advantageously, said frame 52 can be cooled, by creating a hydraulic pipeline inside it and connecting said pipeline to a cooling
10 circuit.

According to one possible embodiment, advantageously, said exchange apparatus 6 also comprises a tube bundle cleaning system.

Preferably said cleaning system is a shaking system,
15 which cleans the surfaces of the tubes of the tube bundles by means of direct or indirect percussion of the tube bundle itself.

Advantageously said cleaning system is mounted near said upper end 12 of the tube bundle 8, preferably inside
20 said collection tank 26, if provided.

In particular, by positioning the cleaning system inside the collection tank, in an area not surrounded by hot or corrosive combustion gases, the duration and reliability of the system are prolonged.

25 Advantageously the cleaning system comprises some bars

which are welded or in any case made integral to the elements of the tube bundle.

Moreover said bars are made integral or connected to one another. A battery of shakers is adapted to shake
5 said bars in order to make the tube bundle elements vibrate.

The heat exchange units described are used in any type of total or partial recovery plant, in other words they are heat exchange apparatus or heat exchangers or
10 heat transformers, adapted to use the residual thermal content of a fluid that is unloaded from any type of plant.

Advantageously they are used in waste incineration plants, in which the fumes produced by the incinerator
15 constitute the 'hot' fluid, in other words the second fluid having a residual thermal content which is intended to be recovered, by transferring it to the first fluid at a lower temperature, known as the coolant.

The combusted gases originating from the
20 incineration of the waste are rich in toxic or polluting powders and therefore, in order to be released into the atmosphere they must be purified.

Normally purifying filters are unable to filter such high temperature gases, as at such temperatures, the
25 toxic substances contained in the gases are extremely

corrosive to the extent that they rapidly deteriorate the filters.

In this type of plants, the units described are particularly advantageous.

5 In actual fact in such incineration plants the fumes produced following waste incineration are directed along a predetermined fume route, through the containing means, for example with suitably insulated channelling systems in order to limit heat loss.

10 Advantageously, the heat exchange units disclosed in the present invention are arranged along said path.

Preferably, the direction systems develop in a horizontal direction, i.e. parallel to the base plane or basement of the plant, whilst the exchange units develop
15 according to a vertical direction, i.e. perpendicular to the direction horizontal to the base plane of the plant.

Such units therefore consent heat exchange between the combustion fumes and a coolant that flows, under natural or artificial circulation, inside tube bundles.

20 Advantageously the first fluid or coolant used is constituted by water in various physical states, and in particular under the form of saturated steam, heated steam or water, depending on whether they are vaporiser units 4', superheater units 4'' or economiser units 4'''.

25 The first fluid that circulates inside the tube

bundle, following heat exchange increases in temperature and can therefore be directed towards a wide range of uses, for example as motor fluid in steam turbine plants or in order to supply a heating unit.

5 It will be appreciated in the above description, that the heat exchange units according to the invention make it possible to overcome the drawbacks encountered in state of the art exchange units.

Unusually the heat exchange units described can be
10 extracted with very simple operations and the extraction operation does not require any destructive cutting of metal sheet and pressurised parts in general, but merely the removal of threaded connections on the flanging connecting the unit with the heat exchange fluids.

15 The fact that no destructive cuts are performed entails further economic advantages, as well as a considerable reduction in technical plant shutdown times, as the welded or replaced pressurised parts must be subject to new checks and testing.

20 A further advantage relates to cleaning operations, as it is possible to use state of the art shaking systems with a technical effect which is unobtainable in the heat exchange units of the previous type.

In actual fact in the known exchange units the tube
25 bundle is linked to the structure of the unit in a rigid

manner, whereby, if subject to hammering, the bundle tubes vibrate slightly and the amount of removed dust is very poor. It should also be considered that dusts often contain residues that make them sticky or viscous and the
5 same therefore almost tend to stick to the outer surfaces of the bundle tubes. The hammering action must therefore be energetic and cause ample tube oscillations, in order to consent adequate cleaning.

The disclosed tube bundle, thanks to the linking
10 systems described, has a considerable elasticity in operation, without requiring disconnection from the exchange unit.

At the same time, in order to guarantee elasticity to the tube bundle, thus preventing it from becoming
15 excessively deformed by the thermal strain caused by the contact with warm gases, particularly advantageous is the arrangement of the tubes, which, in relation to a plane perpendicular to the preferential direction of the bundle, run according to a curve that forms alternating
20 protruding and receding angles.

This configuration, though guaranteeing high flexibility to the tube bundle and therefore an efficient and rapid cleaning of the same by means of shaking systems, is able to guarantee correct relative
25 positioning between the bundle tubes whilst the exchange

unit is in operation, in order not to hamper correct heat exchange between the tubes and outer fluid.

In actual fact if the bundle tubes are excessively frail, a danger exists that under thermal strain the tubes may
5 become excessively deformed and lose their correct alignment in relation to the flow of warm gases, with the consequential reduction in the heat exchange surface between the fluids.

Therefore, the tube bundle described guarantees high
10 unit efficiency in all operating conditions, and consents rapid and accurate removal of the dust covering it, thus guaranteeing maximum cleaning efficiency.

The positioning of the shaker system in an area not surrounded by warm and corrosive gases, allows greater
15 duration of the shaker systems themselves.

A further advantage is that the connection means between the tube bundle and the heat exchange unit do not come into contact with the flow of warm, corrosive gases. Therefore on the one hand such connection means are not
20 subject to any corrosive action that may compromise their duration, and on the other they do not in turn constitute a receptacle for dust, which, as in state of the art units, inevitably tends to fall onto the tubes, thus contributing to the soiling of the bundle.

25 Obviously, those of ordinary skill in the art, in

order to satisfy contingent and specific requirements, can bring about a number of alterations and variants to the heat exchange units described above.

For example, a tube bundle may be provided which is
5 hung on the structure of the heat exchange unit also in an embodiment that does not provide for the use of the collection tank.

Moreover the tube bundle can be linked to the exchange unit even without separation means between the
10 area surrounded by the warm fumes and the area in which the shaking means are located.

Obviously further alterations and variants are possible to the heat exchange units described, all of which remain within the scope of the invention as defined
15 in the following claims.

CLAIMS

1. A heat exchange unit (4',4'',4'''), suitable for performing heat exchange between first and second fluids at different temperatures, comprising a exchange apparatus (6) provided with a tube bundle (8), crossed internally by said first fluid, containing means (10) of said second fluid, suitable for housing said exchange apparatus (6) in such a way that at least one portion of said tube bundle (8) is externally surrounded by said second fluid characterised in that said exchange apparatus (6) comprises connection means (9) structurally separate from said containing means (10) and to which one end of said tube bundle (8) is operatively connected.
2. The heat exchange unit according to claim 1, wherein said connection means (9) extend in a direction that is substantially parallel to said tube bundle (8).
3. The heat exchange unit according to claim 1, wherein said connection means (9) extend in a direction that is substantially perpendicular to said tube bundle (8).
4. The heat exchange unit according to any of the previous claims, wherein said tube bundle (8) comprises at least one inlet opening (16) of the first fluid into the tube bundle (8) and at least one outlet opening (20) of the first fluid from the tube bundle, said inlet

opening(16) and said outlet opening (20) being arranged in correspondence with said connection means (9).

5. The heat exchange unit according to any of the previous claims, wherein said exchange apparatus (6) comprises shaking means (51) of said tube bundle (8), said shaking means (51) being arranged at said connection means (9).

6. The heat exchange unit according to any of the previous claims, wherein said heat exchange apparatus (6) comprises a collection tank (26) arranged at the end of the tube bundle (8) operatively connected to the connection means (9).

7. The heat exchange unit according to claim 6, wherein said collection tank (26) comprises a box-shaped structure that is fluid tight relative to said second fluid.

8. The heat exchange unit according to claims 6 or 7, wherein said collection tank (26) encloses said connection means (9).

9. The heat exchange unit according to any of the previous claims, wherein said heat exchange apparatus (6) rests on said containing means (10).

10. The heat exchange unit according to any of the previous claims, comprising separating means (52,54), interposed between said connection means (9) of the tube

bundle (8) and said containing means (10) suited to guaranteeing a fluid seal between said connection means (9) and said containing means (10).

11. The heat exchange unit according to claim 10,
5 wherein said separating means (52,54) comprise a separating plate (54) at least partially crossed by said tube bundle (8).

12. The heat exchange unit according to claim 11,
wherein said separation plate (54) is solidly fixed to
10 said collection tank (26).

13. The heat exchange unit according to claims 10, 11 or 12, wherein said separating means (52,54) comprise a separation frame (52).

14. The heat exchange unit according to claim 13,
15 wherein said separation frame (52) is integrally fixed to said collection tank (26).

15. The heat exchange unit according to claim 13 or 14, wherein said separating frame (52) is adapted to being connected to a cooling circuit.

20 16. The heat exchange unit according to any of the previous claims, wherein said exchange apparatus (6) comprises hooking means (46), adapted to allowing the handling of said exchange apparatus (6), said hooking means (46) being arranged at the end of the tube bundle
25 (8) operatively connected to the connection means (9).

17. The heat exchange unit according to claim 16, wherein said hooking means (46) comprise at least one eyebolt (47).

18. The heat exchange unit according to any of the
5 previous claims, wherein said tube bundle (8) extends as a coil along a prevalent direction Z.

19. The heat exchange unit according to claim 18, wherein in relation to a plane perpendicular to said prevalent direction Z, said tube bundle (8) extends at
10 least in part along a broken line which forms a series of alternate protruding and receding angles.

20. A steam production plant comprising a heat exchange unit (4',4'',4''') according to any of the previous claims.

15

ICT/IT 03/00358

IPC 7 F28D7/06 F28F9/013 F22B37/20

IPC 7 F22B F28F F28D F28G

EPO-Internal

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 1 099 742 A (V TEPLOTEKHNIЧЕСKY I IM F E D) 17 January 1968 (1968-01-17) the whole document ---	1-6, 18, 20
X	US 5 219 150 A (THOMPSON GUY T ET AL) 15 June 1993 (1993-06-15) column 2, line 23 -column 3, line 57; figures ---	1-4, 6, 7, 9, 16-20
X	FR 1 044 642 A (INDUSTRIKEMISKA AKTIEBOLAGET) 19 November 1953 (1953-11-19) the whole document ---	1-4, 6, 9-11, 16, 18, 20
X	US 3 896 873 A (WOLOWODIUK WALTER ET AL) 29 July 1975 (1975-07-29) the whole document ---	1-3, 6, 7, 9, 10, 18
	--- -/--	

☒ Patent family members are listed in annex.

- "A"** document defining the general state of the art which is not considered to be of particular relevance
- "E"** earlier document but published on or after the international filing date
- "L"** document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O"** document referring to an oral disclosure, use, exhibition or other means
- "P"** document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

14/10/2003

Mootz, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 03/00358

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 722 781 A (BABCOCK & WILCOX LTD) 26 January 1955 (1955-01-26) the whole document -----	1-3, 9, 16-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 03/00358

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 1099742	A	17-01-1968	NONE	
US 5219150	A	15-06-1993	DE 69220445 D1 DE 69220445 T2 EP 0536962 A1	24-07-1997 12-02-1998 14-04-1993
FR 1044642	A	19-11-1953	NONE	
US 3896873	A	29-07-1975	CA 967556 A1 DE 2320082 A1 FR 2183091 A1 GB 1423388 A JP 49061746 A SU 543362 A3	13-05-1975 22-11-1973 14-12-1973 04-02-1976 14-06-1974 15-01-1977
GB 722781	A	26-01-1955	NONE	